

D320 L

Advanced image processing unit that allows you to control up to 4 sources on one LED display.



Seamlessly switch from source to source or display sources together, overlay them, customize them. With analog and digital outputs which allow for the control of displays, as well as built-in-control software, the D320 L gives you control over everything from basic set-up to configuration and advanced feature control.

BARCO

Visibly yours

Technical specifications

Inputs	4 optional inputs Front accessible Integrated video processing Auto sensing, hot swappable s-video, composite, YUV / RGB, SDI, HD-SDI, DVI up to UXGA
Compatibility	Barco LED displays
Output	DVI-D
Flexibility	User defined inputs
Control	through XLite toolset
Scaler	4 input channels [Data-Video] fully independant scalable to desired output resolution
Z-order control	Instant modification of Z-order control, for each output window
Window Positioning	Intuitive positioning interface
Connectors	RS 232 [RJ11]
Effects	Anamorphic imaging Chroma keying [per input] Alpha keying [per input] Z-order control Windowing/ View ports
Size	482mm x 53mm x 486mm
Weight	+/- 7 kg
Operating T°	0°C <-> 45°C
Power	120W max auto ranging 90-264V (50-60 Hz) Connector: 3 pin IEC
Size Input Units	103mm x 41mm x 181mm
Scalability	Chaining for more inputs Stacking for more displays
Order Information	R9850710