

Galaxy 7 Classic+

SXGA+, 7 000 lumens three-chip DLP 3D stereo projector



The Galaxy family has a proven record for active and passive stereo technology. It is the only 3-chip DLP™ projector offering the unrivaled platform for Infitec+™, the superior stereo separation technology combining high contrast with excellent stereo separation.

High Light Output Mode:

7000 ANSI lumens - typical lamp lifetime 1200 hrs (max. 1500 hrs)

Economy Mode:

4650 ANSI lumens - typical lamp lifetime 1700 hrs (max. 2000 hrs)

· SXGA+ resolution 1400 x 1050 · Contrast ratio 1600:1 · 4/3 aspect ratio · Built-in Stereo-Creator™, including DVI sources · i-Blend™ supports up to three channels

BARCO

Visibly yours

Technische Daten

Lichtstrom	4650 ANSI lumens (Economy mode) 7000 ANSI lumens (Normal mode)																														
Auflösung	1400 x 1050 (SXGA+) native resolution																														
Helligkeitsgleichförmigkeit	>90% for the total screen area																														
Kontrast	1600:1 (full white/full black)																														
Lampe	1.2 kW (Xenon illumination system) - 800 W in Economy mode Typical / max. lifetime: 1200 / 1500 hours (Normal mode) 1700 / 2000 hours (Economy mode)																														
Merkmale	Standard: <ul style="list-style-type: none"> • Bi-cubic WARP™ • Synchronous and asynchronous active stereo display • DynaColor™/Linked DynaColor™ • CLO (Constant Light Output)/ Linked CLO • Stereo-Creator • i-Blend™ (two- or three channel) • Economy mode • Shutter Optional: <ul style="list-style-type: none"> • Optical Soft Edge Matching (OSEM) • Infitec™ (Switchable) • External polarization (linear or circular) • GISCU™: multi-system and multi-site color management 																														
Geräuschpegel	< 60 dBA at 40°C < 54 dBA at 20°C																														
Kompatibilität	<ul style="list-style-type: none"> • Active stereo capabilities up to SXGA+ at 118Hz • WARP 6™ based pixel map processor using bi-cubic interpolation algorithms for advanced geometry corrections up to a pixelclock of 205 MHz • All current available video sources in RGB or DVI 																														
Eingänge	1 multifunctional 5-cable input (high bandwidth) for connection of: <ul style="list-style-type: none"> • RGB analog signals with standard sync (BNC connectors), sync on green or separate sync • 1 Stereo sync input (mini DIN) • 2 stereo outputs (coax) • 1 DVI input 																														
Kommunikation	<ul style="list-style-type: none"> • RS232 or RS422 loop-through input (D9-connector) for PC-based projector control • Communication input (D9 connector) for peripherals 																														
Optiken	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Lens type</th> <th style="text-align: left;">order nr.</th> <th style="text-align: left;">throw ratio</th> </tr> </thead> <tbody> <tr> <td colspan="3">Fixed lens (Manual focus)</td> </tr> <tr> <td>TLD (0.8:1) HB*</td> <td>9842040</td> <td>0.75</td> </tr> <tr> <td>TLD+ (1.2:1)</td> <td>9840775</td> <td>1.23</td> </tr> <tr> <td colspan="3">Motorized zoom and focus</td> </tr> <tr> <td>TLD (1.6-2.0:1) HB*</td> <td>9842060</td> <td>1.5 to 1.8</td> </tr> <tr> <td>TLD (2.0-2.8:1) HB*</td> <td>9842080</td> <td>1.8 to 2.6</td> </tr> <tr> <td>TLD (2.8-5.0:1) HB*</td> <td>9842100</td> <td>2.6 to 4.6</td> </tr> <tr> <td>TLD (5.0-8.0:1) HB*</td> <td>9842120</td> <td>4.6 to 7.3</td> </tr> <tr> <td colspan="3">* High brightness lens</td> </tr> </tbody> </table>	Lens type	order nr.	throw ratio	Fixed lens (Manual focus)			TLD (0.8:1) HB*	9842040	0.75	TLD+ (1.2:1)	9840775	1.23	Motorized zoom and focus			TLD (1.6-2.0:1) HB*	9842060	1.5 to 1.8	TLD (2.0-2.8:1) HB*	9842080	1.8 to 2.6	TLD (2.8-5.0:1) HB*	9842100	2.6 to 4.6	TLD (5.0-8.0:1) HB*	9842120	4.6 to 7.3	* High brightness lens		
Lens type	order nr.	throw ratio																													
Fixed lens (Manual focus)																															
TLD (0.8:1) HB*	9842040	0.75																													
TLD+ (1.2:1)	9840775	1.23																													
Motorized zoom and focus																															
TLD (1.6-2.0:1) HB*	9842060	1.5 to 1.8																													
TLD (2.0-2.8:1) HB*	9842080	1.8 to 2.6																													
TLD (2.8-5.0:1) HB*	9842100	2.6 to 4.6																													
TLD (5.0-8.0:1) HB*	9842120	4.6 to 7.3																													
* High brightness lens																															
Lens Shift	Motorized V shift: up to 100% Motorized H shift: up to 65%																														
Leistungsaufnahme	Normal mode: 1700 Watts Economy mode: 1400 Watts																														
Stromversorgung	230V (tolerance 180V - 255V)																														

Umgebungstemperatur	Max. 35°C
Gewicht	Net weight: 124 lbs/56 kg Shipping weight: 210 lbs/95 kg